WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4524
Rec. May 5 1959
Well No.
Permit No.
Do not fill in

Owner: Joseph L. Zeigler Driller: A & B Contractors

Address: 225 E. 4th Ave., Sun Valley, Nev. Address: Sun Valley, Nev. Lic. No. 287

Location of well: ¼ ¼ Sec. , T. N/S, R. E, in Washoe County

or

Water will be used for: domestic Total depth of well: 91'

Size of drilled hole: 6" Weight of casing per linear foot: 7 lbs.

Thickness of casing: 10 ga. Temp. of water: cold

Diameter and length of casing: 6" OD X 91'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 30 GPM

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Mar. 7,59 Date of completion of well: 3/14/59

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	16	16	Broken rock & clay fill
16	55	39	broken rock clay
55	58	3	broken rock, water
58	86	28	broken rock & clay
86	91	5	broken rock & water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 86 to 91 ft.

Other aquifers: 55 to 58'

First water at 55 feet.

Casing perforated
from 50 to 91 ft.

Size of perforations
6 X ¼

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	1	0	91	Black steel

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailer tested 30 GPM.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)

1959 MAY 5 AM 8 55

STATE ENGINEER
OFFICE