LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6-5/8	1	0	104	black steel;gravel packed; clay grout

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

bailer test 30GPM; 10' draw down

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed ..... Well Driller

By .....

License No. .....

Dated ....., 19 .....

(Not to be filled in by Driller)

1959 JUL 27 PM 1 38
OFFICE
STATE ENGINEER

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4727
Rec. July 27 1959
Well No.
Permit No.
Do not fill in

Owner: John Darre Driller: A & B Contractors

Address: Space 27, C&R Trlr. Ct, Reno (395N) Address: Sun Valley, Nev. Lic. No. 208

Location of well: SW ¼ NW ¼ Sec. 26, T. 20 N/S, R. 19 E, in Washoe County

or

Water will be used for: domestic Total depth of well: 104

Size of drilled hole: 6" Weight of casing per linear foot: 12 lbs.

Thickness of casing: 188 ga. Temp. of water: cold

Diameter and length of casing:
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 50½

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: May 17 Date of completion of well: May 30, 1959

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	26	26	boulders and clay
26	32	6	gray clay
32	65	33	white rock & water
65	104	39	gray rock & water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 65 to 104 ft.

Other aquifers

First water at 65 feet.

Casing perforated
from 64 to 104 ft.

Size of perforations
1/8 x 6"

919