

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 4125  
 Rec. July 27 19 59  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner Fred Cutler Driller A & B Contractors

Address P.O. Box 39, Steamboat Address Sun Valley, Nev Lic. No. 208

Location of well: SW 1/4 SE 1/4 Sec. 4, T 17 N/S, R 20 E, in Washoe County

Water will be used for domestic Total depth of well 71

Size of drilled hole 6" Weight of casing per linear foot 12 lbs.

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6-5/8 x 70  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 1 GPM

If flowing well describe control works none  
(Type and size of valve, etc.)

Date of commencement of well June 7 Date of completion of well June 10, 1959

Type of well cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	07	07	black dirt
7	22	15	brown rock and water
22	68	46	red rock
68	71	3	brown rock and flowing water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 68 to 71 ft.

Other aquifers 7 to 22'

First water at 7 feet.

Casing perforated

from 40 to 70 ft.

Size of perforations

1/8 X 6"



