WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4739
Rec. 19
Well No. .....
Permit No. 18023
Do not fill in

Owner: GLEN LYON BROADACRES TRAILER COURT Driller: LOUIS F. EVANS

Address: 2934 Las Vegas Blvd. N. Las Vegas, Nev. Address: 2020 Carroll N. Las Vegas Lic. No. 117

Location of well: ¼ NE ¼ Sec. 13, T. 20 N/S, R 61 E, in Clark County

or .....

Water will be used for: Commercial Total depth of well: 300 ft.

Size of drilled hole: 16" 300 ft. Weight of casing per linear foot: .188 lbs.

Thickness of casing: 3/16 wall Temp. of water .....

Diameter and length of casing: 8 5/8" O.D. 302 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 55 ft.

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: June 4, 1959 Date of completion of well: June 26, 1959

Type of well rig: Keystone

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	silt
5	15	10	brown sandy clay
15	26	11	gray clay
26	30	4	gray clay & gravel
30	36	6	gray clay
36	52	16	brown sandy clay
52	60	8	white hard clay
60	63	3	gray clay & gravel (water)
63	65	2	brown sandy clay
65	76	11	gray clay
76	80	4	brown sandy clay
80	89	9	gray clay
89	101	12	brown sandy clay
101	123	22	gray clay
123	131	8	brown sandy clay
131	138	7	gray clay
138	142	4	brown sandy clay
142	147	5	red sticky clay
147	151	4	brown sandy clay
151	153	2	gravel (water)
153	170	17	brown sandy clay
170	219	49	brown sticky clay
219	230	11	red sticky clay
230	244	14	light brown clay & gravel (water)
244	248	4	porus rock
248	253	5	brown sticky clay
253	260	7	tan clay & gravel (water)

(over)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 270 to 280 ft.

Other aquifers: 60 to 63

151 to 153 230 to 244

253 to 260 267 to 269

292 to 296

First water at 60 feet.

Casing perforated

from 60 to 300 ft.

Size of perforations

½" wide 6" long

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
260	263	3	porus rock
263	264	1	pan clay & gravel
264	266	2	cement gravel
266	267	1	brown sticky clay
267	269	2	gravel (water)
269	270	1	red sticktyclay
270	274	4	red clay & gravel (water)
274	280	6	gravel (water)
280	292	12	red sticky clay
292	296	4	gravel (water)
296	300	4	red sticky clay

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8"	2 above	300	302	gravel packed 250 ft.from 50 ft.to 300 ft.15 yds.gravel cemented 50 ft.from 0 to 50 ft.2½ yds.gravel

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Louis F. Evans
Well Driller

By Louis F.Evans

License No. 117

Dated July 28, 19 59

(Not to be filled in by Driller)