WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4760
Rec. Aug 5 19 59
Well No.
Permit No.
Do not fill in

Owner Donald T. Hall Driller

Address U. S. 50 & Kingsbury Rd. Lake Tahoe Lic. No.

Location of well: NE ¼ NE ¼ Sec. 19, T. 15 N/S, R. 20 E, in Ormsby County

or Stewart Homesite

Water will be used for Domestic Total depth of well 143 feet

Size of drilled hole 8" Weight of casing per linear foot 19 #

Thickness of casing 3/16 " Temp. of water Cool

Diameter and length of casing 8 " I. D. 143 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing

If nonflowing well give depth of standing water from surface 64 Feet

If flowing well describe control works Not Flowing
(Type and size of valve, etc.)

Date of commencement of well June 1, 1959 Date of completion of well June 13, 1959

Type of well rig 71- A Speed Star, Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Sand
4	20	16	Sand & Clay
20	91	71	Clay & Course Sand
91	94	3	Clay
94	110	16	Sand
110	143	33	Course Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 110 to 143 ft.

Other aquifers

First water at 101 feet.

Casing perforated

from 113 to 143 ft.

Size of perforations

1/8" x 4 "

Torch

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 " I. D.	0	143	143	Star Drive Shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well will make 30 G P M @ 120 feet, Boiler Test.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed ..... Well Driller

By Bob Meyer

License No. 10 & 209

Dated July 4, 19 59

(Not to be filled in by Driller)

1959 AUG 5 AM 11 43