WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4767
Rec. Aug 5 1959
Well No.
Permit No.
Do not fill in

Owner: Gus Heinze
Address: Fallon Nevada

Driller: Fred Erb
East Star Route
Address: Fallon Nevada
Lic. No. 121

Location of well: S.E. ¼ S.W. ¼ Sec. 22, T. 19 N/S, R. 28 E, in Churchill County

or

Water will be used for: Stock
Total depth of well: 30 ft.

Size of drilled hole: 6 in.
Weight of casing per linear foot:

Thickness of casing: 20 gauge galvinized
Temp. of water: 60 degrees

Diameter and length of casing: 6" casing 30' long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 7 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: July 15, 1959
Date of completion of well: July 16, 1959

Type of well rig: Cable Tool Well Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sand
8	10	2	Gravel
10	20	10	Adobe
20	30	10	Course Sand

Water-bearing Formation, Casing Perforations, Etc.
Course Sand

Chief aquifer (water-bearing formation)
from 20 to 30 ft.

Other aquifers:

First water at 8 feet.

Casing perforated
from 22 to 30 ft.

Size of perforations
1/64 x 1 In.

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	30	30 ft.	20 gauge galvinized casing & well cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump test about 1000 gallons per. hour

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb
Well Driller

By Mrs Fred Erb

License No. 121

Dated July 20, 1959

(Not to be filled in by Driller)

1959 AUG 5 AM 11 46

OFFICE
STATE ENGINEER