WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 4838
Rec. Sept. 28 19 59
Well No. 17970
Permit No. 25096
Do not fill in

Owner James Williams Driller A & B Contractors

Address ..... Address Sun Valley, Nev. Lic. No. 208

Location of well: S½ ¼NE¼ Sec. 6, T. 20 N/S, R 20 E, in Washoe County

or at Government Springs, North of Sun Valley, Nev.

Water will be used for domestic Total depth of well 40'

Size of drilled hole 6-5/8" Weight of casing per linear foot #14

Thickness of casing 3/16 " Temp. of water cold

Diameter and length of casing 6" X 40'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface SWL 12'

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well Aug. 14 Date of completion of well Aug. 14-59

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	brown sandy clay
25	40	15	gray broken rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 25 to 40 ft.

Other aquifers .....

First water at 25 feet.

Casing perforated
from 30 to 40 ft.

Size of perforations
1/8 X 6"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6-5/8"	1	0	40	Black steel 188 ga. welded joimts.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed at 3 GPM from bottom of hole; SWL 12' from top.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By [illegible]

License No. [illegible]

Dated [illegible], 19[illegible]

(Not to be filled in by Driller)

1959 SEP 28 PM 12 52

OFFICE ENGINEER