WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4856
Rec. Oct. 5 1959
Well No.
Permit No. 15689
030A Do not fill in

Owner: Michel H. Pettibone Driller: H. A. Sevey
Address: Morenci, Aricona Address: Vale, Oregon Lic. No. 250

Location of well: NW 1/4 NW 1/4 Sec. 10, T. 44 N/S, R. 34 E, in Humboldt County
or 66' ~~xxxxxx~~ west of the NW corner and 250' south of the NW corner

Water will be used for: Irrigation Total depth of well: 250'

Size of drilled hole: 16" Weight of casing per linear foot:

Thickness of casing: 3/16 Temp. of water:

Diameter and length of casing: 16" x 226'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 19'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Date of completion of well: Sept. 28, 1959

Type of well rig: Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	16	16	clay
16	20	4	Gravel
20	110	90	~~xxxxxxxx~~ brown clay
110	180	70	sand
180	224	44	pea gravel
224	242	8	clay
242	250	8	gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 110 to 180 ft.

Other aquifers
242 to 250

First water at 30 feet.

Casing perforated
from 184 to 224 ft.

Size of perforations
1/2x2

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16"	0	226	226	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Installed permanent pump Western land Roller pump will pump 2000 gal a min with a 70' drawdown

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No. 258

Dated....., 19.....

1959 OCT 5 AM 10 12

OFFICE

(Not to be filled in by Driller)