WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4863
Rec. Oct 12 1959
Well No.
Permit No.
Do not fill in 089

Owner James C. Robertson Driller J. N. Pitcher Company

Address Washoe Lake Address 9501 S. Virginia Lic. No. 4507

Location of well: ¼ ¼ Sec. 17, T. 16 N/~~S~~, R. 20 E, in County

or Block L Lot 7 Washoe Valley Farms

Water will be used for Domestic Total depth of well 70'

Size of drilled hole 6" Weight of casing per linear foot 18#

Thickness of casing 1/4" Temp. of water 55°

Diameter and length of casing 6" x 70'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 5'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well September 9, 1959 Date of completion of well September 10, 1959

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sand
2	7	5	Hard Pan
7	30	23	Clay and Sand
30	35	5	Green Sand and Some Clay
35	45	10	Clay Sand and Small Gravel
45	70	25	Sand Gravel Some Course Gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 45 to 70 ft.

Other aquifers

First water at 30 feet.

Casing perforated

from 50 to 70 ft.

Size of perforations

1/8 x 6" Torch Cut

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	70	70	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailer Test: approx. 35 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By J. B. Cunningham

License No. 4507

Dated October 9, 19 59

(Not to be filled in by Driller)