

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4864
 Rec. Oct. 12 1959
 Well No.
 Permit No. 18500

Do not fill in

Owner Mrs. Marie Stresley Driller J. N. Pitcher Company

Address Austin, Nevada Address 9501 S. Virginia Lic. No. 4507

Location of well: SE 1/4 NW 1/4 Sec. 13., T. 19. N. 8, R. 41. E. in LANDER ~~Washoe~~ County

Water will be used for Domestic Total depth of well 55' 6"

Size of drilled hole 6" Weight of casing per linear foot 18#

Thickness of casing 3/16 Temp. of water 55°

Diameter and length of casing 6" x 55'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface.....

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well September 4, 1959 Date of completion of well September 9, 1959

Type of well rig Gable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Hard Pan
3	12	9	Sandy Clay
12	20	8	Water Gravel
20	27	7	Water Gravel
27	38	11	Sandy Clay
38	50	12	Water Gravel
50	55	5	Sandy Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 12 to 55 ft.

Other aquifers.....

First water at 12 feet.

Casing perforated
 from 35 to 55 ft.

Size of perforations
1/8" x 6" Torch Cut



