

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4872
 Rec. Oct. 12 1959
 Well No.
 Permit No.
Do not fill in

Owner..... Roy Casazza Driller J. N. Pitcher Company
 Address..... 150 Wolcomb Lane Address. 190 Moana Lane Reno Lic. No. 4507
 Location of well: NE 1/4..... 1/4 Sec. 7, T. 18N/S, R. 20E, in..... Washoe County
 or.....
 Water will be used for..... Domestic Total depth of well..... 250'
 Size of drilled hole..... 6" Weight of casing per linear foot..... 18#
 Thickness of casing..... 1/4" Temp. of water..... Cold
 Diameter and length of casing..... 6" x 250'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....
 If nonflowing well give depth of standing water from surface..... 210'
 If flowing well describe control works.....
 (Type and size of valve, etc.)
 Date of commencement of well..... Sept. 17, 1958 Date of completion of well..... Sept. 23, 1958
 Type of well rig..... Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
Deepening Well			
156	191	35	Clay
191	200	9	Sand
200	210	10	Fine Sand
210	217	7	Clay
217	221	4	Sand
221	230	9	Clay & Gravel
230	235	5	Gravel & Sand
235	240	5	Clay
240	246	6	Sand
246	250	4	Small Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from to ft.

Other aquifers.....

First water at 210 feet.

Casing perforated

from to ft.

Size of perforations



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0156	250	94	Butt welded casing with drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By *[Signature]*
License No. 4507

Dated November 2, 1958, 19

(Not to be filled in by Driller)

NOV 12 1958
STATE ENGINEER
OFFICE