WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4875
Rec. Oct. 12 1959
Well No.
Permit No.
Do not fill in

Owner: L. O. Ranf — Driller: J. N. Pitcher Company

Address: 2120 Spanish Springs Sparks — Address: 190 Moana Lane Reno — Lic. No. 4507

Location of well: ¼ ¼ Sec. 27 (28 33 34), T. 21 N/S, R. 21 E, in Washoe County

or

Water will be used for: Domestic — Total depth of well: 73'

Size of drilled hole: 6" — Weight of casing per linear foot: 18 Lb.

Thickness of casing: 1/4" — Temp. of water: 55°

Diameter and length of casing: 6" x 73'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 12'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: March 28, 1958 — Date of completion of well: April 1, 1958

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Surface soil and large gravel
8	26	18	Sandy clay
26	48	22	Sandstone
48	53	5	Yellow clay
53	73	20	Tight cemented gravel water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 53 to 73 ft.

Other aquifers

First water at 53 feet.

Casing perforated

from 53 to 73 ft.

Size of perforations

1/8" x 6" Torch Cut

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	73	73	Butt welded casing with drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test Approximately 16 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By M. H. Cuerka

License No. 4507

Dated July 10, 1958, 19 58

(Not to be filled in by Driller)