WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4887
Rec. Oct. 19, 1959
Well No.
Permit No.
Do not fill in

Owner Gerald B. Scott & George Gardner Driller J.C. Faretto & Son

Address 1250 Piñon Drive, Reno, Nevada Address 736 Humboldt St. Reno Lic. No. 2

Location of well: NW¼SE¼ Sec. 34, T 18 N/S, R 20 E, in Truckee Meadows, Washoe County

or about 1 mile northeast of Steamboat on old Geiger Grade Road.

Water will be used for Domestic Total depth of well 105 ft

Size of drilled hole 6 inch Weight of casing per linear foot 12.89 Lbs.

Thickness of casing .188 of an inch Temp. of water 62°

Diameter and length of casing Diam O.D. 6 5/8", 8'-00" to 12'-00" lengths.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 46'-05"

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well September 23, 1959 Date of completion of well October 9, 1959

Type of well rig Speed Star 71 Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	Yellow clay with rocks & coarse sand.
28	36	8	Yellow clay with rocks & boulders.
36	40	4	Yellow clay coarse sand & gravel.
40	43	3	Boulder.
43	52	9	Yellow clay with coarse sand & gravel.
52	57	5	Change in color of clay, Coarse sand, gravel, rocks & boulders.
57	60	3	1st water. Water level 46'-08". Trickle of water. Yellow clay with medium sand.
60	65	5	No water. Yellow clay.
65	70	5	2nd water. Water level 46'-02". Little water. Yellow clay with medium sand. Rocks.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 87 to 95 ft.

Other aquifers 82 to 84

First water at 57 feet.

Casing perforated
from 82 to 95 ft.

Size of perforations
3/8" x 1 1/2"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
70	75	5	Yellow clay. Rocks.
75	80	5	3rd water. Fine to medium sand with clay.
80	82	2	Rocks.
82	84	2	4th water. Water level 47'-00". Water. Black sharp edged sand material.
84	87	3	No water. Cemented material. Hard.
87	95	8	5th water. Cemented material. Black sharp edged sand. Hard.
95	105	10	6th water. Very little water. Cemented material. Black sharp edged sand. Hard.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0'-02"	97'-00"	97'-02"	6 5/8" O.D. Black pipe. Welded with 1/4"x3" couplings. Short pattern drive shoe. Perforated with Mills perforator.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

0 to 80 ft sand material black, some light + tan color. This sand material common to ground surface. 80 to 105 ft. sand material sharp edged black rock. Cleaned + bailed well 10 gal per minute 19 ft. drawdown.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J.C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated October 14, 19 59

(Not to be filled in by Driller)

1959 OCT 19 AM 10 23

OFFICE
ENGINEER