

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4919
 Rec. Nov. 9 1959
 Well No.
 Permit No.

Do not fill in

Well # 1

Owner..... Pinkey Driller..... Bob Meyer

Address..... Pine-Nut Lodge, Topaz Lake Address..... 306 Bath St. Carson Lic. No. 209

Location of well: NW 1/4 SW 1/4 Sec. 33, T10 N/S, R22 E, in..... Douglas County
 or..... Topaz Lake

Water will be used for..... Domestic Total depth of well..... 80 feet

Size of drilled hole..... 6 Inch Weight of casing per linear foot..... 13#

Thickness of casing..... 3/16" Temp. of water..... Cool

Diameter and length of casing..... 6 5/8" OD, 80 Feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure..... Not Flowing

If nonflowing well give depth of standing water from surface..... 50 Feet

If flowing well describe control works..... Not Flowing
(Type and size of valve, etc.)

Date of commencement of well..... Oct. 25, 1959 Date of completion of well..... November 1, 1959

Type of well rig..... 71-B Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Boulders & Caly
5	45	40	Sand & CLAY Clay
45	60	15	Boulders
60	80	20	Sand & CLAY Clay

HARVEY & BOB MEYER
 DRILLING CONTRACTORS
 CARSON CITY, NEVADA

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 60 to 80 ft.

Other aquifers.....

First water at..... 60 feet.

Casing perforated
 from 50 to 80 ft.

Size of perforations
1/4" X 3"
Mills



