

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 4920
 Rec. Nov. 9, 1959
 Well No.
 Permit No.
Do not fill in

Owner Pinkey Driller Bob Meyer
 Address Pine Nut Lodge, Topaz Lake Address 306 Bath St. Carson Lic. No. 209
 Location of well: NW 1/4 SW 1/4 Sec. 23, T. 10N/S, R. 22E, in Douglas County
 or Topaz Lake, Nevada
 Water will be used for Domestic Total depth of well 88 Feet
 Size of drilled hole 6 Inch Weight of casing per linear foot 13 #
 Thickness of casing 3/16 Inch Temp. of water Cool
 Diameter and length of casing 6 5/8" OD, 88 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing
 If nonflowing well give depth of standing water from surface 58 Feet
 If flowing well describe control works Not Flowing
 (Type and size of valve, etc.)
 Date of commencement of well Nov. 1, 1959 Date of completion of well Nov. 4, 1959
 Type of well rig 71-B Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	9	9	Boulders & Caly
9	50	41	Sand & EE Clay
50	60	10	Sand, EEI Clay & Boulders
60	88	28	Sand & Clay

HARVEY & BOB MEYER
 DRILLING CONTRACTORS
 CARSON CITY, NEVADA

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 70 to 80 ft.

Other aquifers.....

First water at 70 feet.

Casing perforated
 from 88 to 60 ft.

Size of perforations
1/4" X 3"
Mills



