

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 4927  
 Rec. Nov. 2, 1959  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in 12068

Owner BENNETT SMITH Driller BILL WOLGAMOTT

Address ANDORNA NEVADA Address PO BOX 12 OROVADA Lic. No. 292

Location of well: NE 1/4 NW 1/4 Sec 3, T41 N/S, R37 E, in HUMBOLT CO County

Water will be used for STOCK WATER Total depth of well ~~175~~ 175

Size of drilled hole 10' Weight of casing per linear foot 21

Thickness of casing 3/16 Temp. of water 56

Diameter and length of casing 10 1/2" 125 ft  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Aug 10 Date of completion of well 25 Aug 20

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Top Soil
4	26	22	Large Rocks Clay
22	49	27	Loose Gravel Sand
49	72	23	Rocky Sandy Clay
72	125	53	Loose Gravel
125	175	50	Cemented Gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 72 to 125 ft.

Other aquifers \_\_\_\_\_

---

First water at 72 feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

