WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4978
Rec. Dec 1 1959
Well No.
Permit No. 17695
Do not fill in

Owner Woodrow Erickson Driller Chet Ufeaver

Address Winnemucca Address Osvada Lic. No. 207

Location of well: [illegible] Sec. 29, T. 43 N/S, R. 37 E, in Humboldt County

or

Water will be used for Irrigation + Dom Total depth of well 280

Size of drilled hole 16" Weight of casing per linear foot 7/16

Thickness of casing 7/16 Temp. of water

Diameter and length of casing 16" x 304 ft.

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 27 ft.

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well Nov 20 Date of completion of well Dec 10th

Type of well rig Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Top soil
18	70	52	Sandy clay
70	85	15	Gravel
85	105	20	Yellow Clay
105	125	20	Sand + Gravel
125	165	40	Yellow Clay.
165	190	25	Sand + Gravel
190	220	30	Yellow Clay
220	230	10	Packed sand + Gravel
230	280	50	Yellow Clay.
280	?		Sand + Gravel.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 280 to ? ft.

Other aquifers

105 to 125

165 to 190

First water at 34 feet.

Casing perforated

from 120 to 190 ft.

Size of perforations

½ x 2½

(OVER)

919

LOG OF FORMATIONS—Continued

From Feet	To Feet	Thickness	Type of material

CASING RECORD

Diameter Casing	Depth Set	To Feet	Length	"Remarks"—Seals, Grouting, Etc.
16"	0	204	204	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Chet Weaver
Well Driller

By Chet Weaver

License No. 254

Dated Dec 15, 1958

(Not to be filled in by Driller)

1959 DEC 1 AM 11 42