

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5003  
 Rec. Jan. 26 1960  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Harry Walsh Driller A & B CONTRACTORS

Address \_\_\_\_\_ Address Sun Valley, Nev Lic. No. 287

Location of well: 1/4 S. 1/4 Sec., T. N/S, R. E, in Washoe County  
 or \_\_\_\_\_

Water will be used for domestic Total depth of well 199'

Size of drilled hole 6" Weight of casing per linear foot 12 lbs.

Thickness of casing 188 ga. Temp. of water cold

Diameter and length of casing 6" X 197'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 100'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Oct. 11-59 Date of completion of well Oct. 16-59  
cable tool

Type of well rig \_\_\_\_\_

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Sandy top soil
12	25	13	hard pan & sand
25	160	135	sandy clay
160	186	26	muddy clay
186	198	12	hard decomposed granite
198	199	1	hard granite

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 186 to 198 ft.

Other aquifers \_\_\_\_\_

160'

First water at 160 feet.

Casing perforated

from 140 to 197 ft.

Size of perforations

1/8" X 6"



