

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5015
 Rec. Feb. 1 1960
 Well No.
 Permit No.
Do not fill in

Owner Millard Artlip Driller A. & B Contractors
 Address 795 Lupin Dr., Sun Valley, Nev. Address Sun Valley, Nevada Lic. No. 287
 Location of well: SE 1/4 NE 1/4 Sec. 18, T. 20. N/8, R. 20. E, in Washoe County
 or
 Water will be used for domestic Total depth of well 165'
 Size of drilled hole 6" Weight of casing per linear foot 7 lbs.
 Thickness of casing 12 ga. Temp. of water cold
 Diameter and length of casing 6" X 165'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....
 If nonflowing well give depth of standing water from surface 90'
 If flowing well describe control works.....
 (Type and size of valve, etc.)
 Date of commencement of well Nov. 2-59 Date of completion of well Nov. 5-59
 Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sandy top soil
8	25	17	hard pan
25	107	82	decomposed granite
107	158	51	sandy clay
158	165	7	hard decomposed granite

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 107 to 158 ft.

Other aquifers.....

First water at 107 feet.

Casing perforated
 from 105 to 165 ft.

Size of perforations
1/8 X 6"



