

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5018  
 Rec. Feb. 1 1960  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner M. R. Biswell Driller A & B Contractors

Address Ranger Rs., Panther Valley, Nev. Address Sun Valley, Nev. Lic. No 287

Location of well: NE 1/4 SW 1/4 Sec. 23, T. 20 N/8, R. 19 E, in Washoe County \_\_\_\_\_  
 or \_\_\_\_\_

Water will be used for domestic Total depth of well 153'

Size of drilled hole 6" Weight of casing per linear foot 19'

Thickness of casing 1/4" Temp. of water cold

Diameter and length of casing 6" X 145'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 80'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Dec. 28-59 Date of completion of well Jan.-60

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Rocky clay
10	85	75	brown rock
85	97	12	andicite
97	142	45	hard black andicite
142	153	11	grey ash

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 97 to 142 ft.

Other aquifers \_\_\_\_\_

First water at 97 feet.

Casing perforated from 100 to 145 ft.

Size of perforations 1/8 X 8"



