

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5049  
 Rec. FEB. 17 19 60  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner Joseph W. Cummings Driller Harvey & Bob Meyer  
 Address Box 4, Crystal Bay Lake Tahoe Address 306 Bath St., Carson Lic. No. 10  
 Location of well: SW 1/4 NE 1/4 Sec. 7, T. 15N/S, R. 20E, in Ormsby County  
 or Brush Property, Winnie Lane, Carson City  
 Water will be used for Test & Domestic Total depth of well 130 feet  
 Size of drilled hole 8 Inch Weight of casing per linear foot 22.36#  
 Thickness of casing .250 Inch Temp. of water Cool  
 Diameter and length of casing 8 5/8" OD, 130 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing  
 If nonflowing well give depth of standing water from surface 19 feet  
 If flowing well describe control works Not Flowing  
(Type and size of valve, etc.)  
 Date of commencement of well August 18, 1959 Date of completion of well August 30, 1959  
 Type of well rig 71-B Speed Star, Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	2	2	Top Soil ( sandy )	
2	9	7	Sand	Chief aquifer (water-bearing formation) from <u>42</u> to <u>120</u> ft.
9	22	13	Sand & Clay	Other aquifers.....
22	26	4	Clay	
26	28	2	Sand	
28	42	14	Clay & Sand	
42	120	78	Water Sand	First water at <u>42</u> feet.
120	130	10	Dry sand & Clay	Casing perforated from <u>42</u> to <u>120</u> ft.
HARVEY & BOB MEYER DRILLING CONTRACTORS CARSON CITY, NEVADA				Size of perforations <u>1/8" X 4"</u>
				<b>Mills</b>



