WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5072
Rec. FEB. 19 1960
Well No.
Permit No. 17807
Do not fill in

Owner: Dominic Asmundi
Driller: B & B Drilling Co. Inc.
Address: Duckwater, Nye Co. Nevada
Address: Provo, Utah
Lic. No. 193

Location of well: SW ¼ SW ¼ Sec. 34, T. 1[illegible] N/S, R. 5[illegible] E, in [illegible] County

or

Water will be used for: Irrigation
Total depth of well: 202

Size of drilled hole: 14 inch
Weight of casing per linear foot: [illegible]

Thickness of casing: 1/4
Temp. of water

Diameter and length of casing: 14 inch I.D. 200 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 7 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: October 20, 1959
Date of completion of well: Oct. 30, 1959

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	[illegible]		Surface
[illegible]	27		Clay
27	74		Sand
74	50		Clay & Boulders
50	97		Sand & Gravel
97	119		Clay & Boulders
119	160		Gravel Sand & Boulders
160	173		Clay & Boulders
173	202		Boulders

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 119 to 160 ft.

Other aquifers

First water at 20 ft. feet.

Casing perforated
from 40 to 200 ft.

Size of perforations
1/4 inch

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Ronald Bradshaw
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)

1960 FEB 19 AM 8 56

ENGINEER

OFFICE