

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 5077  
 Rec. 3-3 19 60  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Henry Dreyer Driller A. & B. CONTRACTORS

Address Gardnerville, Nevada Address Sun Valley, Nev. Lic. No. 287

Location of well: E 1/4 SE 1/4 Sec. 30, T. 13N/S, R. 21E, in Douglas County

Water will be used for domestic Total depth of well 106'

Size of drilled hole 5-5/8" Weight of casing per linear foot 7 lbs.

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 5-5/8" X 106'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 6'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Feb. 7-60 Date of completion of well Feb. 10-60

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Sandy top soil
10	48	38	loose sand
48	101	53	sandy clay
101	106	6	fine gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
101                      106  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.  
 Other aquifers 10 to 48

---

First water at 10 feet.

---

Casing perforated  
 from 60 to 106 ft.

---

Size of perforations  
1/8" X 6"

