LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6	0	85	85	Butt welded casing with drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test Approximately 20 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By J. W. Cunningham

License No. 3692

Dated May 20, 1959, 19

(Not to be filled in by Driller)

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5108
Rec. MAR. 28 1960
Well No.
Permit No.
Do not fill in

Owner: Mr. Puliver — Driller: J. N. Pitcher Company

Address: Louitt Valley Nevada — Address: 190 Moana Lane Reno — Lic. No. 3692

Location of well: SW ¼ NW ¼ Sec. 26, T20 N/S, R19 E, in Washoe County

or

Water will be used for: Domestic — Total depth of well: 85'

Size of drilled hole: 6" — Weight of casing per linear foot: 10#

Thickness of casing: .188 wall — Temp. of water: 50°

Diameter and length of casing: 6" x 85'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 10'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: April 10, 1959 — Date of completion of well: April 14, 1959

Type of well rig: Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Bolders
6	30	24	Clay
30	50	20	Yellow Sandstone
50	60	10	Fine Sandstone (Gray)
60	75	15	Cemented Sand
75	80	5	Small Gravel
80	85	5	Gray Sandstone and Gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 7 75 to 80 ft.

Other aquifers

First water at 75 feet.

Casing perforated

from 65 to 85 ft.

Size of perforations

1/4" Torch Cut