

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5125  
 Rec. April 11 1960  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Frank J. ... Driller ...  
 Address ... Address ... Lic. No. 289  
 Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec 12, T. 15 N/S, R. 20 E, in Ormsby County  
 or ...  
 Water will be used for Domestic Total depth of well 360  
 Size of drilled hole 12" Weight of casing per linear foot 10 lbs. small  
 Thickness of casing 10 ga Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" - 300'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure. ✓  
 If nonflowing well give depth of standing water from surface 20 5/8'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Dec 10 - 59 Date of completion of well Jan 4 - 60  
 Type of well rig Rotary

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	...
5	10	5	...
10	15	5	...
15	20	5	...
20	25	5	...
25	30	5	...
30	35	5	...
35	40	5	...
40	43	3	...

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 86 to 343 ft.  
 Other aquifers 130 - 26

---

First water at 22 feet.

Casing perforated  
 from 40 to 230 ft.

Size of perforations  
3/16" x 1 1/2" Rotary



