WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5177
Rec. May 25 1960
Well No.
Permit No. 19753
Do not fill in

Owner: Panaca Ward L.D.S. Church Driller: Darell Free

Address: Panaca, Nevada Address: Caliche, Nevada Lic. No. 30

Location of well: S.E. ¼ N.E. ¼ Sec. 7, T. 2 N/S, R. 68 E, in Lincoln County

or

Water will be used for: Irrigation Total depth of well: 135'

Size of drilled hole: 14" 115' 7" 20' Weight of casing per linear foot:

Thickness of casing: 10 gauge Temp. of water:

Diameter and length of casing: 14" 116
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 18'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: April 29, 1960 Date of completion of well: May 23, 1960

Type of well rig: Colmun Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	60	60	sandy Clay
60	98	38	gravel
98	115	17	sand and gravel in clay
115	135	20	sand and gravel in clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 60 to 98 ft.

Other aquifers

First water at 18 feet.

Casing perforated
from 88 to 116 ft.

Size of perforations
1/8 X 10"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well tested producing 900 gal per min at 60'
gravel packed to 75' 7" hole
recommended pump 800 gals. from 60'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Darell Free
Well Driller

By Owner

License No. 30

Dated May 23, 1968

1960 MAY 25 AM 11 00

STATE ENGINEER
OFFICE

(Not to be filled in by Driller)