LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 in	0	95	95	Sealed with Drilling Mud TO 50
				FT. Does NOT Leak.
				SANITARY well seal installed ON
				TOP.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

1 1/2 HR. PUMP INSTALLED PUMPING 60 GPM.
2 hr. TEST WELL DRAWDOWN APP. 1 FT.
QUALITY OF WATER Excellent.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed M. E. Nichols
Well Driller

By.....

License No. 271

Dated 5/2/60, [redacted]

(Not to be filled in by Driller)

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5179
Rec. MAY 4 1960
Well No.
Permit No. 18092.
Do not fill in

Owner: FORd F. BURKE
Driller: Sonoma Drilling Co.
Address: 500 Hoge Rd. Reno
Address: RT. 1 CARSON CITY Lic. No. 271

Location of well: ¼ ¼ Sec. 27, T. 20 N/S, R. 19 E, in W Ashoe County
or MT. DIABLO MERIDIAN SO. 1/2 N.W. 1/4 S.W. 1/4 N.E. 1/4

Water will be used for: DOMESTIC - USE/IRR Total depth of well: 125 FT.

Size of drilled hole: 8 IN. INSIDE Weight of casing per linear foot: 12GA.

Thickness of casing: Temp. of water: ——

Diameter and length of casing: 8 IN. INSIDE 95 FT. LONG
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 80 FT.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: NOV. 24/1958 Date of completion of well: DEC. 12/1958

~~Type of well rig~~ ~~CABLE~~ TOOL

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30		Yellow clay - HARd
30	32	2	Light GRAvel
32	35	3	Yellow clay - HARd
35	39	4	BROKen Rock
39	48	9	Yellow clay
48	50	2	Rock shelF
50	65	15	Yellow clay - HARd
65	70	5	BROKen Rock
70	90	20	Rock shelF
90	95	5	SAND stone - white
95	110	15	BROKen Rock
110	120	10	1ST. WATER - STRONg
			IN GREen shale
120	125	5	GREen shale

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 95 to 120 ft.

Other aquifers: NONE

First water at 110 feet.

Casing perforated
from 85 to 95 ft.

Size of perforations
FACTORY PERFORATIONS
1 1/2" X 1/8"

(OVER)