WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5191
Rec. May 23 19 60
Well No.
Permit No.
Do not fill in

Owner: Fred Frey Driller: A & B Contractors, L. Smith

Address: Verdi, Nevada Address: Sun Valley, Nev. Lic. No. 208

Location of well: NW ¼ NW ¼ Sec. 17, T. 19 N/S, R. 18 E, in Washoe County

or

Water will be used for: domestic Total depth of well: 106'

Size of drilled hole: 6" Weight of casing per linear foot: 15 lbs.

Thickness of casing: 5/16" Temp. of water: cold

Diameter and length of casing: 6" X 106'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: 20 GPM

If nonflowing well give depth of standing water from surface: SWL 30'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 4-4-60 Date of completion of well: 4-6-60

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	27	27	Brown sandy clay & boulders
27	63	34	grey clay & sand
63	68	5	gravel & water
68	99	31	blue hard clay
99	106	7	grey hard clay & water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 99 to 106 ft.

Other aquifers: 63-68

First water at 63 feet.

Casing perforated

from 63 to 103 ft.

Size of perforations

1/8" X 6"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	1	106'	Black steel; welded joints.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail test 20 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A & B Contractors
Well Driller

By M. Gatlin

License No. 987

Dated May 20, 1960

(Not to be filled in by Driller)