

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5192  
 Rec. MAX 23 1960  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner ~~James O'Doan~~ XXXX O'Doan Driller A. & E. Contractors, M. Artlip  
 Address Box 17, Black Spgs., Nev. Address Sun Valley, Nev. Lic. No. 287  
 Location of well: SE 1/4 SW 1/4 Sec 26, T 22 N/S, R 19 E, in Washoe County  
 or Lot #67, Hepner Subd. #2

Water will be used for domestic Total depth of well 112'

Size of drilled hole 6" Weight of casing per linear foot 9 lbs.

Thickness of casing 156 ga. Temp. of water cold

Diameter and length of casing \_\_\_\_\_  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 3-28-60 Date of completion of well 3-30-60

Type of well rig cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	17	17	Loose sandy top soil	
17	25	8	hard pan	
25	44	19	sandy clay	Chief aquifer (water-bearing formation)
44	74	30	loose sand & water	from <u>74</u> to <u>76</u> ft.
74	76	2	rocky clay	Other aquifers <u>44'</u>
76	93	17	loose heavy sand	<u>93-100'</u>
93	100	7	sand & gravel	
100	112	12	brown sandy clay	
				First water at <u>44</u> feet.
				Casing perforated
				from <u>70</u> to <u>103</u> ft.
				Size of perforations
				<u>1/8" x 6"</u>



