


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 5264
 Rec. APRIL 28 1960
 Well No. 18502
 Permit No. 16468
Do not fill in

Owner WM. EARL POLLARD Driller _____

Address EUREKA Address _____ Lic. No. _____

Location of well: SE 1/4 SE 1/4 Sec. 8., T22N18, R54E, in EUREKA County _____
 or Plugged under NOZ 61581 N39,802341 W 115,906590 NAD27

Water will be used for IRRIGATION Total depth of well _____

Size of drilled hole _____ Weight of casing per linear foot _____

Thickness of casing _____ Temp. of water 60°

Diameter and length of casing _____
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface _____

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well _____ Date of completion of well _____

Type of well rig _____

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material | Water-bearing Formation, Casing Perforations, Etc. |
|-----------|-------------------------------|----------------|--|--|
| 0 | 12 | 12 | Course Sand. | |
| 12 | 21 | 9 | Fine Sand | Chief aquifer (water-bearing formation) |
| 21 | 50 | 29 | Block Mud. | from _____ to _____ ft. |
| 50 | 60 | 10 | Quick Sand. | Other aquifers _____ |
| 60 | 70 | 10 | Clay and Mud | _____ |
| 70 | 100 | 30 | Dark Clay & Sand. | _____ |
| 100 | 126 | 26 | Gray Tuff Shale. | _____ |
| 126 | 126 ¹³⁵ | 9 | Block Mud & Sand. | _____ |
| 135 | 155 | 20 | Gravel & Course Sand Lots of water. | First water at _____ feet. |
| | | | | Casing perforated |
| | | | | from _____ to _____ ft. |
| | | | | Size of perforations _____ |

Eureka, Nevada
March 30, 1960

Mr. Wm. Earl Pollard
Eureka, Nevada

Dear Mr. Pollard:

On March 18, 1960 we tested the well located on
SE $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 8 T22N R54E MDB&M in Eureka
county and found the following results:

Pumping 1200 GPM the draw down was from
8' to 50' - Temp. of the water was 60°.

EUREKA FARM SUPPLY
Vernon A. Manz

COPIES
RECEIVED

1960 APR 28 AM 11 24

14468