

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

✓ Log No. 5263  
 ✓ Rec. JUNE 15 1960  
 Well No. ....  
 Permit No. 12155  
*Do not fill in*

Owner Francis McKay Driller J. N. Pitcher Co.

Address 385 Boone Rd., Salem, Oregon Address 9501 So. Virginia St. Lic. No. 232

Location of well: NW 1/4 SW 1/4 Sec. 12., T35 N/S, R. 23 E. in Washoe County  
or .....

Water will be used for Irrigation Total depth of well 200 Ft.

Size of drilled hole 16" Weight of casing per linear foot 44 lbs.

Thickness of casing 1 1/8" Temp. of water 60

Diameter and length of casing 16 1/2" x 200'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure non-flowing

If nonflowing well give depth of standing water from surface 25'

If flowing well describe control works none  
(Type and size of valve, etc.)

Date of commencement of well 4/28/60 Date of completion of well 5/2/60

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	Sandy loam
28	40	12	Dry Gravel
40	62	12	Sandy Clay
62	68	6	Fine Water Sand
68	125	57	Med. to Large Gravel
125	130	5	Fine silt
130	150	20	Med. Gravel
150	164	14	Fine silt
164	170	6	Med. Gravel
170	194	24	Fine silt Some Small Gravel
194	200	6	Silty Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 58 to 125 ft.

Other aquifers all gravel

strata below 28'

First water at 62 feet.

Casing perforated

from 0 to 170 ft.

Size of perforations

3/16" x 2"

RECEIVED  
 1960 JUN 13 AM 9 43



