Need Log

5339

Log No. 5339
Rec. Aug 1 1960
Well No.
Permit No. 18761
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

18761 →

W. H. & E. C. Flicke

Owner: Desert Palms Trailer Court — Driller: Phelps Pump & Equipment

Address: — Address: 400 College Ave. N.L.V. Lic. No. 98

Location of well: SE ¼ NE ¼ Sec 13, T20N/S, R61E, in Co

or 2960 L.V. Blvd. No.

Water will be used for: Trailer Park — Total depth of well: 350'

Size of drilled hole: 15" — Weight of casing per linear foot: 12.20

Thickness of casing: (8 5/8 OD x 352') 10 ga. Temp. of water

Diameter and length of casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 51 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: June 16, 1960 — Date of completion of well: June 24, 1960

Type of well rig: Shadrick Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	39'	39'	Caliche - Clay
39'	56'	17'	Gravel water
56'	350'	294'	Caliche - clay & streaks of gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 150' to 350' ft.

Other aquifers 39' - 56'

First water at 43' feet

Casing perforated

from 150 to 350' ft.

Size of perforations

Torch

OFFICE
STATE ENGINEER
AUG 1 1960

(OVER)

910

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8	0	270		
8 ¼ plus	2	358		Grouted to 50' gravel packed bottom portion

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Phelps Pump & Equipt. Co.
Well Driller

By: Lloyd R. Lemon

License No. 98

Dated July 15, 1960

(Not to be filled in by Driller)

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Kind of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" I.D.	0	207	207	Bottom 30 feet of 8" casing is heavy Quarter inch wall casing. Drive shoe on Bottom.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 20 G.P.M. could not lower water level.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed S. E. McKinney & Son
Well Driller

By S. E. McKinney

License No. 45

Dated July 25, 1957

(Not to be filled in by Driller)

OFFICE STATE ENGINEER
OCT 15 57
RECEIVED