18942
Refer to note

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 53 72
Rec. Aug. 29 1960
Well No. X
Permit No. 18942
Do not fill in

Owner: GEORGE CANON Driller: E.R. BAXTER & H DRLG.

Address: JACK POT, NEVADA (CONTACT) Address: CARSON CITY, NEV. Lic. No. 322

Location of well: NE ¼ SW ¼ Sec. 1, T. 41 N/S, R. 64 E, in ELKO County

or

Water will be used for: BAR + RESTERAUNT Total depth of well: 260

Size of drilled hole: 7 ¼ Weight of casing per linear foot: 20 GA.

Thickness of casing: 20 GA. Temp. of water: NORMAL

Diameter and length of casing: 6" X 250'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 65'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 5/15/60 Date of completion of well: 5/16/60

Type of well rig: PORTA DRILL (ROTARY)

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	220	220	FINE S.S.
220	250	30'	COURSE SAND + GRAVEL
250	260	10	SANDY CLAY

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 220 to 250 ft.

Other aquifers

First water at 65' feet.

Casing perforated

from 220 to 250 ft.

Size of perforations

LOUVERED (SLOTS)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	250	250	GRAVEL PACKED + SEALED

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

PLENTY OF WATER FOR REQUIRED USE

5 HP 3 PHASE Motor

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Pat H Oil Co
Well Driller

By F. R. Foster

License No. 6072

Dated Aug 1, 1960

1960 AUG 29 AM 10 27

STATE ENGINEER
OFFICE

(Not to be filled in by Driller)