WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5397
Rec. SEPT 13 1960
Well No.
Permit No.
Do not fill in

Owner Church of Jehovah's Witness Driller Fred Exh

Address Fallon Nevada Address East Star Route Fallon Nevada Lic. No. 121

Location of well: SW ¼ SW ¼ Sec. 6, T. 18 N/S, R. 29 E, in Churchill County

or

Water will be used for Domestic Total depth of well 22 ft.

Size of drilled hole 6 inch Weight of casing per linear foot

Thickness of casing 20 gauge Galvanized Temp. of water 58°

Diameter and length of casing 6 inch Casing 22 ft. long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Aug 2 1960 Date of completion of well Aug 2 1960

Type of well rig Cable Tool Well Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	adobe
8	17	9	Fine Sand
17	18	1	adobe
18	22	4	Small Gravel

Water-bearing Formation, Casing Perforations, Etc.
Small gravel & Sand

Chief aquifer (water-bearing formation)
from 18 to 22 ft.

Other aquifers

First water at 9 feet.

Casing perforated
from 16 to 22 ft.

Size of perforations
1 x 1/64 in

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 in	0	22	22 ft.	20 gauge galvanized casing 4 weld cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 900 gal per hr

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By [illegible]

License No. [illegible]

Dated Sept 12, 1960

(Not to be filled in by Driller)

1960 SEP 13 AM 9 12

STATE ENGINEER
OFFICE