

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

I

Log No. 5401
 Rec. SEPT 12 1960
 Well No. _____
 Permit No. _____

Owner Ray Holloway Driller W. E. Blain
5019 El Ranchos Drive, Spaw 24
 Address Sparks, Nevada Address Box 255 Carson City Lic. No. 301

Location of well: NE 1/4 NE 1/4 Sec. 32, T. 28 N/S, R. 20 E, in Washoe County

or 300 ft West of Intersection of Pyramid Lake Road & Wedekind Road
75 ft south of Wedekind Road, Sparks, Nevada

Water will be used for Domestic Total depth of well 103

Size of drilled hole 10" to depth of 52 ft Weight of casing per linear foot # 8.81 lb

Thickness of casing 10 gage Temp. of water Cold

Diameter and length of casing 6" x 104 ft
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. _____

If nonflowing well give depth of standing water from surface 49 ft

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 8-22-60 Date of completion of well 8-26-60

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	soil
3	32	29	Yellow clay + Rocks
32	35	3	Gravel
35	52	17	yellow clay
52	54	2	sand
54	68	14	yellow clay
68	84	16	gravel
84	96	12	clay
96	102	6	gravel
102	103	1	clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 96 to 102 ft.

Other aquifers 52-54
68-84

First water at 52 feet.

Casing perforated

from 84 to 104 ft.

Size of perforations

5" x 1/8"

