

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5405
 Rec. SEPT 14 1960
 Well No. _____
 Permit No. _____
Do not fill in

Owner Chas. H. Branstetter - P.O. Box 1106 Driller B + H. DRILL CO.

Address CARSON CITY, NEV. Address CARSON CITY, NEV. Lic. No. 322

Location of well: $\frac{1}{4}$ Sec. $\frac{1}{4}$, T. N/S, R. E, in ORMSBY CO. County
 or East 264' of n⁷ of S⁷ of NE⁷ of NW⁷ of NW⁷ of Sec 32, T 15 N, R 20 E. MDBRM

Water will be used for DOMESTIC USE Total depth of well 165'

Size of drilled hole 8 1/2" Weight of casing per linear foot 10 GAUGE

Thickness of casing 10 GA. Temp. of water NORMAL

Diameter and length of casing 6" X 145'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. _____

If nonflowing well give depth of standing water from surface 70'

If flowing well describe control works. _____
(Type and size of valve, etc.)

Date of commencement of well SEPT. 5 Date of completion of well SEPT. 8

Type of well rig PORTA DRILL (ROTARY)

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	70	70	FINE SAND - CLAY @ 65-70
70	85	15	COURSE WATER SAND.
85	120	35	FINE SAND
120	145	25	COURSE SAND - GRAVEL.
145	165	20	FINE SAND - CLAY

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 120 to 145 ft.

Other aquifers.....

VERY LITTLE SURFACE WATER.

First water at 70' feet.

Casing perforated
 from 125 to 145 ft.

Size of perforations
1/32" X 3" Slots



