

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

Log No. 5407  
 Rec. Aug 19 1960  
 Well No. \_\_\_\_\_  
 Permit No. 17665  
 Do not fill in



Owner Lyle Beebe C. F. Wright Driller J. R. McKinney & Son  
 Address 217 Shadow St., Las Vegas Address 1047 S. Main Las Vegas No. 45  
 Location of well: SW 1/4 SW 1/4 Sec. 26 T. 21 N/S, R. 41 E, in Clark County  
 or Government Lot # 26 or Part of Lot # 24 NW 1/4 of SW 1/4 of Sec 1 of 28-21-61  
 Water will be used for Domestic Total depth of well 150 ft.  
 Size of drilled hole 12" to 50 ft., 10" to 150 Weight of casing per linear foot 28 lb.  
 Thickness of casing 1/4" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 150 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 13 ft.  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well March 2, 1955 Date of completion of well March 4, 1955  
 Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	sand
2	6	4	caliche
6	14	8	red sandy clay
14	22	8	caliche water
22	30	8	red sandy clay
30	36	6	caliche
36	45	9	red sandy clay
45	53	8	caliche
53	60	7	sand and gravel
60	65	5	sand and gravel water
65	115	50	red sandy clay
115	119	4	red sand water
119	125	6	red sandy clay
125	130	5	red sandy water
130	150	20	red sand with sandstone shales water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) 150  
 from 125 to 150 ft.

Other aquifers 115 to 119  
60 to 65

First water at 14 ft.

Casing perforated  
 from 100 to 150 ft.

Size of perforations:  
3/16" x 10"

