WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5429
Rec. Oct. 10 1960
Well No.
Permit No.
Do not fill in

Owner Riggins + Tatum Cattle Co. Inc Driller Fred Erb.
Address H 117 Fallon Nevada Address E Star Rte Fallon Nev Lic. No. 121
Location of well: SE 1/4 SW 1/2 Sec. 6, T. 17 N/S, R. 28 E, in Churchill County
or
Water will be used for Domestic Total depth of well 23 ft.
Size of drilled hole 6 inch Weight of casing per linear foot
Thickness of casing 20 gauge Galvinized Temp. of water 62°
Diameter and length of casing 6 inch casing 18 ft of cased well
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 5 ft.
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well Sept 7-1960 Date of completion of well Sept 8, 1960
Type of well rig Cable Tool Well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	adobe
6	12	6	Course Sand
12	23	11	Small layers of adobe & Sand mixture

Water-bearing Formation, Casing Perforations, Etc.
Sand

Chief aquifer (water-bearing formation)
from 6 to 12 ft.
Other aquifers 12 to 23 ft Small layers of Sand and adobe mixture

First water at 6 feet.

Casing perforated
from 6 to 12 ft.

Size of perforations
1 x 1/64 in.

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6in.	0	18	18 ft.	of 20 gauge Galvanized Casing + well cap. Last 5 feet of well filled with gravel (18 to 23 ft.)

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 700 gal. per hr.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb
Well Driller

By Mrs. Fred Erb

License No. 121

Dated Sept 20, 1960

(Not to be filled in by Driller)

1960 OCT 10 AM 9 36
STATE ENGINEER
OFFICE