WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5432
Rec. Oct. 10 1960
Well No.
Permit No.
Do not fill in

Owner John Miller Driller Fred Erb.

Address Fallon Nevada Address E Star Rte Fallon Nev Lic. No. 121

Location of well: SE ¼ NE ½ Sec. 23, T. 18 N/S, R 28 E, in Churchill County

or

Water will be used for Domestic Total depth of well 24 ft,

Size of drilled hole 6 inch Weight of casing per linear foot

Thickness of casing 20 gauge Galvinized Temp. of water 58°

Diameter and length of casing 6 in Casing 24 ft long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 7 ft,

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Sept 24 1960 Date of completion of well Sept 25, 1960

Type of well rig Cable Tool well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	Loam
7	12	5	Course Sand
12	14	2	adobe
14	24	10	Sand

Water-bearing Formation, Casing Perforations, Etc.
Sand

Chief aquifer (water-bearing formation)
from 14 to 24 ft.

Other aquifers

First water at 7 feet.

Casing perforated
from 18 to 24 ft.

Size of perforations
1 x 1/64 in

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6in.	0	24	24ft	20 gauge Galvinized Casing & Well Cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 600 gal. per hr.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb
Well Driller

By Mrs Fred Erb

License No. 121

Dated Sept 28, 1960

(Not to be filled in by Driller)

1960 OCT 10 AM 9 36

STATE ENGINEER
OFFICE