

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5482
 Rec. Oct. 25 1960
 Well No.
 Permit No.
Do not fill in

Owner James Bauska Driller A & B Contractors (G. Rahier)
 Address Sparks, Nev. Address Sun Valley, Nev/. Lic. No. 69

Location of well: SW 1/4 NE 1/4 Sec. 11, T. 17N/8, R. 19E, in Washoe County
 or

Water will be used for domestic Total depth of well 187'

Size of drilled hole 6" Weight of casing per linear foot 14 lbs.

Thickness of casing 1/4" Temp. of water cold

Diameter and length of casing 6" X 187'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 62'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 5-6-60 Date of completion of well 5-17-60

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Boulders, sandy clay
25	50	25	decomposed granite
50	54	4	firm sandy clay
54	78	24	sandy clay, caving
78	90	12	firm sandy clay
90	110	20	sandy clay, boulders, gravel
110	148	38	sharp white sand & gravel
148	180	32	decomposed granite
180	187	7	decomposed granite, turning solid.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

75 to 78

from to ft.

Other aquifers 110 to 148

180-187

75

First water at feet.

Casing perforated

from 130 to 180 ft.

Size of perforations

1/8 X 6"



