

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5495
 Rec. Oct 25 1960
 Well No.
 Permit No.
Do not fill in

Owner Don Bruner Driller A & B Contractors (C.Pu;ati)

Address Washoe Valley, Nev Address Sun Valley, Nev. Lic. No. 207

Location of well: NE 1/4 SW 1/4 Sec. 30., T. 17N/S, R. 20 E, in Washoe County

Water will be used for domestic Total depth of well 104

Size of drilled hole 6" Weight of casing per linear foot 12 lbs.

Thickness of casing 1.88 ga. Temp. of water cold

Diameter and length of casing 6 1/2" X 104'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface..... 60'

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well 8-27-60 Date of completion of well 8-29-60

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Loose sand
2	8	6	black dirt & rocks
8	50	42	hard pan
50	104	54	decomposed granite; loose sand stratas

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 104 ft.

Other aquifers.....

First water at 50 feet.

Casing perforated

from 60 to 104 ft.

Size of perforations

1/16X 6" 4 rows



