

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5500
 Rec. Oct. 25 1960
 Well No.
 Permit No.
Do not fill in

Owner Roy Brown Driller A. & B Contractors (Geo. Rahier)
 Address Gardnerville, Nev. Address Sun Valley, Nev. Lic. No. 69
 Location of well: NE 1/4 SW 1/4 Sec. 19, T. 12N/S, R. 20E, in Douglas County
 or
 Water will be used for domestic Total depth of well 135'
 Size of drilled hole 8" Weight of casing per linear foot 32 lbs
 Thickness of casing 188 ga Temp. of water cold
 Diameter and length of casing 8" X 132'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure 11GPM
 If nonflowing well give depth of standing water from surface SWL 90'
 If flowing well describe control works
(Type and size of valve, etc.)
 Date of commencement of well 7-23-60 Date of completion of well 7-28-60
 Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	Dry gravel & boulders
28	32	4	gravel silt & boulders
32	48	16	silt & clay
48	56	18	sand & silt
56	103	47	silt & clay
103	108	5	sand & gravel water
108	128	20	silt, sand & water
128	135	7	rotten clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 103 to 135 ft.

Other aquifers.....

First water at 103 feet.

Casing perforated
90 129
 from toft.

Size of perforations
1/8 X 6"



