

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5507  
 Rec. Oct 25 1960  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner R.L. Boatright Driller A & B Contractors (C. Pulati)

Address 1650 Dayton Dr., Sparks, Nev. Address Sun Valley, Nev. Lic. No. 207

Location of well: NW 1/4 NE 1/4 Sec. 4, T19 N/S, R. 20E, in Washoe County  
 or .....

Water will be used for domestic Total depth of well 63' 60

Size of drilled hole 6" Weight of casing per linear foot 12 lbs.

Thickness of casing 1/4" Temp. of water cold

Diameter and length of casing 6" X 63' 60'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 5' 8'

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well 10\* 8-8-60 Date of completion of well 8-11-60

Type of well rig cable tool

### LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|------------------|
| 0         | 6       | 6              | tight grey sand  |
| 6         | 23      | 17             | clay & boulders  |
| 23        | 29      | 6              | loose gravel     |
| 29        | 37      | 8              | tight gravel     |
| 37        | 59      | 22             | loose gravel     |
| 59        | 61      | 2              | grey clay        |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 37 to 59 ft.

Other aquifers .....

First water at 23 feet.

Casing perforated  
 from 40 to 55 ft.

Size of perforations

1/16 X 6"



