

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5528  
 Rec. Nov 7 19 60  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Clarence Elquist Driller Harry Bolton

Address Oakley Idaho Address Twin Falls Idaho Lic. No 179

Location of well: <sup>NW</sup> ~~S~~ ~~W~~ <sup>NE</sup> ~~SW~~ <sup>25</sup> ~~1/4~~ ~~1/4~~ Sec. 23, T45 N/3, R68 E, in Elko County County

or \_\_\_\_\_

Water will be used for Stock Water Total depth of well 301'

Size of drilled hole 8" to 14' 6" to 301 Weight of casing per linear foot 19

Thickness of casing 1/4" Temp. of water \_\_\_\_\_

Diameter and length of casing 1 5/8" 6" I.D. 49'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 120'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Sep 12, 1960 Date of completion of well Sep 26, 1960

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	42	42	Clay & gravel
42	145	103	Rhyolite
145	250	105	Limestone
250	301	53	Limestone broken

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 250 to 301 ft.

Other aquifers Drilling water  
at 63'

First water at 63 feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

