WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5563
Rec. Nov. 14, 1960
Well No.
Permit No.
Do not fill in

Owner: Mr. Dick Reno — Driller: J. N. Pitcher Company

Address: 805 S. Wells Avenue — Address: 9501 S. Virginia St. — Lic. No. 232

Location of well: ¼ ¼ Sec., T.20 N/S, R20 E, in Washoe County

or Sec. 28, 29, 32, 33. Lot 14

Water will be used for: Domestic — Total depth of well: 132'

Size of drilled hole: 6" — Weight of casing per linear foot: 9 1/2 lbs

Thickness of casing: 1/4" — Temp. of water: 55

Diameter and length of casing: 6" X 132'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: Non-flowing

If nonflowing well give depth of standing water from surface: ~~####~~ 45'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: October 10, 1960 — Date of completion of well: October 14, 1960

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	70	70	Clay & Boulders
70	132	62	Broken Rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65 to 132 ft.

Other aquifers

First water at 60 feet.

Casing perforated

from 112 to 132 ft.

Size of perforations

Torch Cut 1/8 X 6

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	132	132	Butt welded Casing with Drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailor tested approx. 10 G.P.M.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By M. Cuesta

License No. 232

Dated October 26, 19 60

(Not to be filled in by Driller)

1960 NOV 14 AM 9 55

ENGINEER
OFFICE