

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5592
 Rec. Dec-5 1960
 Well No.
 Permit No.
Do not fill in

Owner W. L. Wattersaw Driller W. E. Blain
 Address Hail Hill Zephyr Cove Nevada Address Box 255 Carson City Lic. No. 301
 Location of well: $\frac{1}{4}$ $\frac{1}{4}$ Sec. 4, T. 15 N/8, R. 20E, in Ormsby County
 or 5 miles West of Carson Air Post on unnamed Road 200 ft south of Road
 Water will be used for domestic Total depth of well 80 ft
 Size of drilled hole 10" to depth of 15 ft Weight of casing per linear foot 8.81 lbs
 Thickness of casing 1/4 gage Temp. of water cold
 Diameter and length of casing 6" x 80 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....
 If nonflowing well give depth of standing water from surface 6 ft
 If flowing well describe control works.....
(Type and size of valve, etc.)
 Date of commencement of well 11-9-60 Date of completion of well 11-11-60
 Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	soil	
3	13	10	yellow clay	Chief aquifer (water-bearing formation)
13	15	2	sand	from <u>72</u> to <u>76</u> ft.
15	40	25	clay	Other aquifers <u>13-15 ft</u>
40	43	3	sand	<u>54-56 ft</u>
43	54	11	clay	
54	56	2	sand	
56	72	16	clay	
72	76	4	sand	
76	80	4	clay	
				First water at <u>13</u> feet.
				Casing perforated
				from <u>6 ft</u> to <u>80</u> ft.
				Size of perforations
				<u>5" x 1/8"</u>



