

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5618
 Rec. DEC. 12. 1960
 Well No.
 Permit No.
Do not fill in

Owner DICK MAGEE Driller Carruthers Drilling Service

Address AUSTIN, NEVADA Address Beowawe, Nevada Lic. No. 116

Location of well: NE 1/4 NE 1/4 Sec. 9., T. 21N/S, R. 46E, in LANDER County
 or

Water will be used for Stock Total depth of well 32

Size of drilled hole 12 " Weight of casing per linear foot

Thickness of casing 1/4" Temp. of water Cold

Diameter and length of casing 12-3/4
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 Ft

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well October 15, 1960 Date of completion of well October 20, 1960

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	9	9	Surface Clay
9	18	9	Hard Sand (water)
18	22	4	Clay
22	27	5	Conglomerate
27	32	5	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 9 to 18 ft.

Other aquifers 27 - 32

First water at 9 feet.

Casing perforated
 from 15 to 32 ft.

Size of perforations

1/2 x 3"



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12-3/4	0	32	32	Casing landed on Bottom

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Carruthers Drilling Service
Well Driller

By [Signature]

License No. 116

Dated Dec 9, 1960

(Not to be filled in by Driller)

1960 DEC 12 AM 9-27

ENGINEER
OFFICE