WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5624
Rec. Dec. 12 1960
Well No.
Permit No. 17782
Do not fill in

Owner KINGSBURY WATER COMPANY Driller OLEY LAWSON

Address ZEPHYR COVE, NEVADA Address TAHOE VALLEY, CALIF. Lic. No.

Location of well: NE ¼ SE ¼ Sec. 23, T. 13 N/S, R. 18 E, in DOUGLAS County

or

Water will be used for QUASI-MUNICIPAL & DOMESTIC Total depth of well 209 feet

Size of drilled hole 12 inch to 51'-3" ~~158 feet 10 inch~~ Weight of casing per linear foot

Thickness of casing 10 guage Temp. of water 40 degrees

Diameter and length of casing 12 inch to 51-3" outer casing for water seal 10 inch to 51'-3" with shoe in granite.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface water stands at 30 feet from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Jan. 1958 Date of completion of well May 24, 1958

Type of well rig Shop built cable rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	18	18	top soil
18	20½	2½	clay
20½	30	9½	hard granite
30	37	7	gravel and sand
37	41½	4½	clay
41½	52	10½	soft rock
52	63	11	white granite
63	68	5	soft granite
68	108	40	gravel and sand
108	130	22	soft granite
130	133	3	rock
133	193	60	soft granite
193	209	16	gravel and sand

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from ~~193'~~ 68' to ~~209'~~ 108' ft.

Other aquifers 41½ to 52
soft rock

First water at 41½ feet.

Casing perforated
from 169 to 209 ft.

Size of perforations
1/8 by 2 "

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12"	surface	51	51'	Outer casing used to seal off surface water, Grouting to 10inch inter casing
10"	51'	209	158'	Inter casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well was test pumped for 24 hour period after water cleared. Well produced 42 gallons per minute during this test.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature]
Well Driller

By Kingsbury Water Co.

License No.

Dated May 24, 1958

(Not to be filled in by Driller)

1960 DEC 12 AM 10 29

STATE ENGINEER
OFFICE