

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 5644
 Rec. JAN. 20 19 61
 Well No.
 Permit No. 20203
Do not fill in

Owner R. J. Summers Driller Tholke Peterson

Address 305 East Ave. Sun Valley Address P.O. Box 663 Sparks Lic. No. 334

Location of well: S 1/2 Sec 1, NE 1/4 Sec 19, T22N/R20E, in Washoe County

Water will be used for Domestic Total depth of well 146 ft

Size of drilled hole 6 5/8" Weight of casing per linear foot 10.9

Thickness of casing 3/16" Temp. of water

Diameter and length of casing 6 1/4" x 22" length set 145 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 34'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well 12/16/60 Date of completion of well 12/19/60

Type of well rig 29 T Bucyrus Erie Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3'	3'	top soil
3'	65'	62'	clay & gravel
65'	85'	20'	sand & rock
85'	146'	61'	D. G.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65' to 142' ft.

Other aquifers Water bearing sand at 65' - 85' to 146' D. G. water bearing

First water at 65' feet.

Casing perforated

from 60' to 145' ft.

Size of perforations

3/16" hor slit 4" long



