

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5645  
 Rec. JAN. 20 1961  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Ted Linke Driller Thorke Petersen  
 Address 455 Sidehill Dr E.V. Address Box 663 Sparks Lic. No. 334  
 Location of well: E 1/4 1/4 Sec. 18., T.20N/S, R.20E, in Washoe County  
 or Sun Valley  
 Water will be used for domestic Total depth of well 108 ft  
 Size of drilled hole 6 5/8 Weight of casing per linear foot 10.9  
 Thickness of casing 3/16" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 6 1/4" x 22 length set : 09 ft  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 30  
 If flowing well describe control works. \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well 1/1/61 Date of completion of well 1/2/61  
 Type of well rig 29T Bucyrus Erie Cable Rig

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	top soil
1	95	94	gavel in clay
95	108	13	D. G.

Water-bearing Formation, Casing Perforations, Etc.  
 Chief aquifer (water-bearing formation)  
 from 40 to 108 ft.  
 Other aquifers Water bearing D.G. from 95 ft to 108  
 First water at 40 feet.  
 Casing perforated  
 from 35 to 108 ft.  
 Size of perforations  
3/16" Hor slits 4"

